

# SAFETY DATA SHEET

Issue Date 12-Jul-2012

Revision Date 06-Jan-2023

Version 3

## 1. PRODUCT AND COMPANY IDENTIFICATION

### Product identifier

**Product Code** 19010  
**Product Name** Grease Blaster

### Other means of identification

### Recommended use of the chemical and restrictions on use

Use only for the purpose on the product label.

### Details of the supplier of the safety data sheet

#### Manufacturer / Manufactured For

Detergent Services, Inc.  
2607 Talina Way  
Houston, TX 77080  
Phone (713) 868-2094

#### Emergency telephone number

24 Hour Emergency Phone Number: 1-800-535-5053

## 2. HAZARDS IDENTIFICATION

### Classification

Skin corrosion/irritation	Category 1 Sub-category A
Serious eye damage/eye irritation	Category 1

### Label elements

#### Emergency Overview

#### Danger

#### Hazard statements

May be harmful if swallowed  
Causes severe skin burns and eye damage



**Appearance** Viscous, Clear, Colorless

**Physical state** Liquid

**Odor** No Information available

#### Precautionary Statements - Prevention

Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

#### Precautionary Statements - Response

Specific Treatment (See Section 4 on the SDS).

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting.

#### Precautionary Statements - Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from reactive metals and acids. Keep locked up and out of the reach of children.

#### Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant.

#### Hazards not otherwise classified (HNOC)

##### Other Information

Unknown Acute Toxicity

2 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Sodium Hydroxide	1310-73-2	5-10	*
2-(2-butoxyethoxy)ethanol	112-34-5	1-5	*
Monoethanolamine	141-43-5	1-5	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

#### First aid measures

##### Skin Contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse. If irritation persists or burns occur, get medical attention. For minor skin contact, avoid spreading material on unaffected skin. For severe burns, immediate medical attention is required.

##### Eye contact

Keep eye wide open while rinsing. Do not rub affected area. Immediate medical attention is required. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes.

##### Inhalation

If mists/vapors are formed or irritation occurs, leave area and do not return until mists/vapors have dissipated. If breathing is difficult, give oxygen. If breathing has stopped, give artificial respiration. Get medical attention immediately.

##### Ingestion

Immediate medical attention is required. Rinse mouth. Do NOT induce vomiting. Drink plenty of water. Never give anything by mouth to an unconscious person.

##### Self-protection of the first aider

Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

#### Most important symptoms and effects, both acute and delayed

##### Symptoms

May cause irritation and/or burning to eyes and skin. Ingestion causes acute irritation and burns to the mucous membranes of the mouth, trachea, esophagus and stomach. Inhalation may cause irritation or burning to mucous membranes.

#### Indication of any immediate medical attention and special treatment needed

##### Note to physicians

Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media** Caution: Use of water spray when fighting fire may be inefficient.

### Specific hazards arising from the chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating and toxic gases and vapors. In the event of fire and/or explosion do not breathe fumes.

**Hazardous combustion products** Contact with metals in presence of moisture will produce hydrogen gas, which can form explosive mixture in air.

### Explosion data

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Evacuate personnel to safe areas. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak.

### Environmental precautions

**Environmental precautions** Do not allow into any sewer, on the ground or into any body of water. Should not be released into the environment. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

### Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Dilute material with dilute acetic acid to a pH of less than 10.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Advice on safe handling** Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation, especially in confined areas. In case of insufficient ventilation, wear suitable respiratory equipment. Use only with adequate ventilation and in closed systems.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep out of the reach of children. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in properly labeled containers.

**Incompatible materials** Metals such as aluminum, tin, lead and zinc especially in the presence of moisture. Incompatible with strong acids and bases. Incompatible with oxidizing agents. Aluminum.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### **Exposure Guidelines**

This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Sodium Hydroxide 1310-73-2	Ceiling: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup> (vacated) Ceiling: 2 mg/m <sup>3</sup>	IDLH: 10 mg/m <sup>3</sup> Ceiling: 2 mg/m <sup>3</sup>
2-(2-butoxyethoxy)ethanol 112-34-5	TWA: 10 ppm inhalable fraction and vapor	-	-
Monoethanolamine 141-43-5	STEL: 6 ppm TWA: 3 ppm	TWA: 3 ppm TWA: 6 mg/m <sup>3</sup> (vacated) TWA: 3 ppm (vacated) TWA: 8 mg/m <sup>3</sup> (vacated) STEL: 6 ppm (vacated) STEL: 15 mg/m <sup>3</sup>	IDLH: 30 ppm TWA: 3 ppm TWA: 8 mg/m <sup>3</sup> STEL: 6 ppm STEL: 15 mg/m <sup>3</sup>

NIOSH IDLH *Immediately Dangerous to Life or Health*

#### **Other Information**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

### Appropriate engineering controls

#### **Engineering Controls**

Showers, Eyewash stations & Ventilation systems.

### Individual protection measures, such as personal protective equipment

#### **Eye/face protection**

Tight sealing safety goggles. Face protection shield.

#### **Skin and body protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

#### **Respiratory protection**

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators or air purifying respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

#### **General Hygiene**

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Keep away from food, drink and animal feeding stuffs. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Avoid contact with skin, eyes or clothing. Take off all contaminated clothing and wash it before reuse. Wear suitable gloves and eye/face protection.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	Liquid
<b>Appearance</b>	Viscous, Clear, Colorless
<b>Odor</b>	No Information available
<b>Odor threshold</b>	No Information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	11.5 - 12.5	1% solution
Specific Gravity	1.146	
Viscosity	No Information available	<b>Remarks</b>
Melting point/freezing point	No Information available	
Boiling point / boiling range	> 212 / ° F Degrees	
Flash point	N/A	
Evaporation rate	< 1	(butyl acetate = 1)
Flammability (solid, gas)	No Information available	

Upper flammability limit:	N/K
Lower flammability limit:	N/K
Vapor pressure	N/A
Vapor density	N/A
Water solubility	N/A
Partition Coefficient (n-octanol/water)	No Information available
Autoignition temperature	No Information available
Decomposition temperature	No Information available

**Other Information**

Density Lbs/Gal	No Information available
VOC Content (%)	9.02

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

Contact with metals in presence of moisture will produce hydrogen gas, which can form explosive mixture in air.

**Conditions to avoid**

Exposure to air or moisture over prolonged periods.

**Incompatible materials**

Metals such as aluminum, tin, lead and zinc especially in the presence of moisture. Incompatible with strong acids and bases. Incompatible with oxidizing agents. Aluminum.

**Hazardous Decomposition Products**

Thermal decomposition can lead to release of irritating and toxic gases and vapors.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**

<b>Product Information</b>	The primary effects and toxicity of this material are due to its corrosive nature.
<b>Inhalation</b>	Causes burns.
<b>Eye contact</b>	Corrosive to the eyes and may cause severe damage including blindness.
<b>Skin Contact</b>	The product causes burns of eyes, skin and mucous membranes.
<b>Ingestion</b>	Causes burns. May be harmful if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Water 7732-18-5	> 90 mL/kg ( Rat )	-	-
Sodium Hydroxide 1310-73-2	= 325 mg/kg ( Rat )	= 1350 mg/kg ( Rabbit )	-
2-(2-butoxyethoxy)ethanol 112-34-5	= 5660 mg/kg ( Rat )	= 2700 mg/kg ( Rabbit )	-
Monoethanolamine 141-43-5	= 1720 mg/kg ( Rat )	= 1000 mg/kg ( Rabbit )	> 1.3 mg/L ( Rat ) 6 h
Propylene Glycol 57-55-6	= 20 g/kg ( Rat )	= 20800 mg/kg ( Rabbit )	-
Sodium Xylene Sulfonate	= 1000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	-

1300-72-7			
Sodium Chloride 7647-14-5	= 3 g/kg ( Rat )	> 10 g/kg ( Rabbit )	> 42 mg/L ( Rat ) 1 h
Sodium Sulfate 7757-82-6	> 10000 mg/kg ( Rat )	-	> 2.4 mg/L ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** No Information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Corrosivity** Causes burns. Extremely corrosive and destructive to tissue. Risk of serious damage to eyes.

**Sensitization** No Information available.

**Germ cell mutagenicity** No Information available.

**Carcinogenicity** No Information available.

**Reproductive toxicity** No Information available.

**STOT - single exposure** No Information available.

**STOT - repeated exposure** No Information available.

**Chronic toxicity** Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Avoid repeated exposure. Possible risk of irreversible effects.

**Target organ effects** Central nervous system, EYES, Respiratory system, Skin.

**Aspiration hazard** No Information available.

**Numerical measures of toxicity - Product Information**

**Unknown Acute Toxicity** 2 % of the mixture consists of ingredient(s) of unknown toxicity.  
The following values are calculated based on chapter 3.1 of the GHS document .

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

0.5% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Sodium Hydroxide 1310-73-2	-	45.4: 96 h Oncorhynchus mykiss mg/L LC50 static	-
2-(2-butoxyethoxy)ethanol 112-34-5	100: 96 h Desmodemus subspicatus mg/L EC50	1300: 96 h Lepomis macrochirus mg/L LC50 static	100: 48 h Daphnia magna mg/L EC50
Monoethanolamine 141-43-5	15: 72 h Desmodemus subspicatus mg/L EC50	114 - 196: 96 h Oncorhynchus mykiss mg/L LC50 static 300 - 1000: 96 h Lepomis macrochirus mg/L LC50 static 227: 96 h Pimephales promelas mg/L LC50 flow-through 3684: 96 h Brachydanio rerio mg/L LC50 static 200: 96 h Oncorhynchus mykiss mg/L LC50 flow-through	65: 48 h Daphnia magna mg/L EC50
Propylene Glycol 57-55-6	19000: 96 h Pseudokirchneriella subcapitata mg/L EC50	41 - 47: 96 h Oncorhynchus mykiss mL/L LC50 static 51400: 96 h Pimephales promelas mg/L LC50 static 51600: 96 h Oncorhynchus mykiss mg/L LC50 static 710: 96 h Pimephales promelas mg/L LC50	1000: 48 h Daphnia magna mg/L EC50 Static
Sodium Chloride 7647-14-5	-	5560 - 6080: 96 h Lepomis macrochirus mg/L LC50 flow-through 12946: 96 h Lepomis macrochirus mg/L LC50 static	340.7 - 469.2: 48 h Daphnia magna mg/L EC50 Static 1000: 48 h Daphnia magna mg/L EC50

		6020 - 7070: 96 h Pimephales promelas mg/L LC50 static 7050: 96 h Pimephales promelas mg/L LC50 semi-static 4747 - 7824: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 6420 - 6700: 96 h Pimephales promelas mg/L LC50 static	
Sodium Sulfate 7757-82-6	-	3040 - 4380: 96 h Lepomis macrochirus mg/L LC50 static 13500: 96 h Lepomis macrochirus mg/L LC50 13500 - 14500: 96 h Pimephales promelas mg/L LC50 6800: 96 h Pimephales promelas mg/L LC50 static	2564: 48 h Daphnia magna mg/L EC50 630: 96 h Daphnia magna mg/L EC50

**Persistence and degradability**

No Information available.

**Bioaccumulation**

No Information available.

Chemical Name	Partition coefficient
2-(2-butoxyethoxy)ethanol 112-34-5	1
Monoethanolamine 141-43-5	-2.3

**Other adverse effects**

No Information available.

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods**

<b>Disposal of wastes</b>	Disposal should be in accordance with applicable regional, national and local laws and regulations.
<b>Contaminated packaging</b>	Do not reuse container.
<b>US EPA Waste Number</b>	D002

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Sodium Hydroxide 1310-73-2	Toxic Corrosive

**14. TRANSPORT INFORMATION**

The shipping classification information in this section (Section 14) is meant as a guide to the overall classification of the product. However, transportation classifications may be subject to change with changes in package size. Consult shipper requirements under 49 CFR, IATA and IMDG to assure regulatory compliance.

**DOT**

**DOT Proper Shipping name** UN1760, Corrosive liquid, n.o.s. (contains sodium hydroxide and monoethanolamine), 8, PG II

**15. REGULATORY INFORMATION****International Inventories**

**TSCA** Complies

DSL/NDSL	Complies
EINECS/ELINCS	Does not comply
ENCS	Does not comply
IECSC	Does not comply
KECL	Does not comply
PICCS	Does not comply
AICS	Does not comply

**Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory.

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List.

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances.

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical Name	SARA 313 - Threshold Values %
2-(2-butoxyethoxy)ethanol - 112-34-5	1.0

**SARA 311/312 Hazard Categories**

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

**CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Sodium Hydroxide 1310-73-2	1000 lb	-	-	X

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Sodium Hydroxide 1310-73-2	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

**US State Regulations****California Proposition 65**

This product does not contain any Proposition 65 chemicals.

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Sodium Hydroxide 1310-73-2	X	X	X
2-(2-butoxyethoxy)ethanol 112-34-5	X	-	X
Monoethanolamine	X	X	X



141-43-5			
Propylene Glycol 57-55-6	X	-	X
Sodium Sulfate 7757-82-6	-	X	X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not Applicable

**16. OTHER INFORMATION**

**HMIS**                      **Health hazards** 3              **Flammability** 0              **Physical hazards** 0              **Personal protection** X

**Legend**

**N/A** - Not Applicable  
**N/E** - Not Established  
**N/D** - Not Determined  
**N/K** - Not Known

**Issue Date**                      12-Jul-2012  
**Revision Date**                      06-Jan-2023  
**Revision Note**                      New format

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**